

## Technical data

(for standard equipment)



### Machine

Minimal length, overall	4,71	m
Minimal length, overall without basket	4,00	m
Minimal width, overall	0,78	m
Minimal height, travel position	1,99	m
Total weight	1950	kg
Live load in traveling position	3,2	kN/m <sup>2</sup>
Live load in work position	2,16	kN/m <sup>2</sup>

### Boom system

Max. working height with 200 kg	14,90	m
Max. working height with 400 kg	-	m
Side reach with 80 kg	6,40	m
Side reach with 200 kg	6,40	m
Side reach with 400 kg	-	m
Max. basket load limit	200	kg
Basket rotation	-	°
Basket dimension (LxWxH)	1,2 x 0,7 x 1,1	m
Movable jib	150	°
Carriage rotation	355	°
Carriage rotation, one side narrow	-	°
Carriage rotation, both side narrow	-	°

### Outrigger

Width, outriggers deployed max./min.	3	2,85	m
One side narrow, out. depl. max./min.	-		m
Both side narrow, out. depl. max./min.	-		m
Outrigger foot (LxW)	0,19 x 0,16		m
To be jacked up to ground slope of	8,4	14,8	°   %
Max. ground clearance	22		cm

### Track system

Height and width track adjustment	9,5	20	cm
Gradeability	19,8	36	°   %
Slope angle	16	28	°   %
Chain (LxW)	145 x 20		cm
Travel speed	1,5		km/h
Max. ground clearance	27		cm

### Engine

Manufacturer	Kubota-Diesel Z-482		
Horse Power	9,9	13,5	kw   PS
Fuel tank capacity	8/Diesel		l

### Engine optional

Manufacturer electric motor	EMG-EBS 90 L X 4-50Hz		
230 V	12,9	2,2	A   kw
400 V	-	-	A   kw

Version (date):

14.10.2010

We reserve the right to make technical alterations! All measurements are rounded.

## Technical data

(for standard equipment)

# LE15GT

## Working envelope

